

High Build Clear Sanding Sealer CW-2001

General Description

A 100% Acrylic non-yellowing water-based sanding sealer. Offering a durable high build finish with excellent sandability and hold out.

Physical Properties

Vehicle Type	Water Emulsion
Solids by Volume	31.73 (+/-1%)
Solids by Weight	34.67 (+/-1%)
VOC	96 g/l
Flash Point	N/A
Specific Gravity	1.03
Viscosity	35 sec. Zahn #2

Application

Application Method	May be sprayed with conventional, airless, and air assisted-airless.
Mixing Instructions	Ready to Spray. May be mixed with tap water as needed.
Substrate Preparation	The surface must be clean, dry and free of grease, oil, dirt, fingerprints and any other contamination to ensure proper adhesion. Remove any loose or peeling paint. Sand basecoat with 320-400 grit sandpaper. May be applied over acrylic, nitrocellulose and UV Basecoat. Test for adhesion and compatibility before full scale application.
Application Instructions	IMPORTANT: Mix well using a power agitator prior to application. Upon application, the temperature of the product, substrate, and coating should be above 50°F. Apply up to 3 coats, allowing enough drying time between coats.
Coverage	Approx. 500 square feet per gallon at 1 dry mil. @ 100% transfer efficiency. Actual coverage may vary depending on application technique, equipment, and weather conditions.

Curing / Drying Time Properties

Air Dying Time (77°F, 50% Humidity)	Flash-off	10 minutes
Dust Free	10-15 min.	No more than 120 Degrees F
Sand	20-25 min.	10 minutes
Package	12 hours	

Force Dry time

Features / Advantages

- Excellent Hardness
- Fast Drying
- For Sealer Applications

Recommended For

- General Purpose Interior.
- Interior Doors
- Kitchen Cabinets
- Interior Shutters & Moldings

Safety / Clean Up

Please read the product Safety Data Sheet and product label before using product. Applications tools must be cleaned with water after use. Dispose of any leftover materials in accordance with local, state, or federal regulations.