

## **Water Based High Build Clear Sanding Sealer**

### **CW-2001**

#### **General Description**

A 100% Acrylic non-yellowing water-based sanding sealer. Offering a durable high build finish with excellent sandability and hold out.

#### **Physical Properties**

Vehicle Type	Water Emulsion
Solids by Volume	31.73 (+/-1%)
Solids by Weight	34.67 (+/-1%)
VOC	96 g/l
Flash Point	N/A
Specific Gravity	1.03
Viscosity	35 sec. Zahn #2

#### **Application**

Application Method	Can be sprayed with conventional, airless, and air assisted-airless.
Mixing Instructions	Ready to Spray. May be mixed with distilled water as needed.
Substrate Preparation	The surface must be clean, dry and free of grease, oil, dirt, fingerprints and any other contamination to ensure proper adhesion. Remove any loose or peeling paint. Sand basecoat with 320-400 grit sandpaper. May be applied over acrylic, nitrocellulose and UV Basecoat. Test for adhesion and compatibility before full scale application.
Application Instructions	IMPORTANT: Mix well using a power agitator prior to application. Upon application, the temperature of the product, substrate, and coating should be above 65°F. Apply up to 3 coats, allowing enough drying time between coats.
Coverage	Approx. 500 square feet per gallon at 1 dry mil. @ 100% transfer efficiency. Actual coverage may vary depending on application technique, equipment, and weather conditions.

#### **Curing / Drying Time Properties**

		<b>Force Dry time</b>
Air Dying Time (77°F, 50% Humidity)		Flash-off 10 minutes
Dust/Tack Free	20-25 min.	No more than 120 Degrees F
Sand & Recoat	30-45 min.	10 minutes
Package	12 hours	

#### **Features / Advantages**

- Excellent Hardness
- Fast Drying
- For Sealer Applications

#### **Recommended For**

- General Purpose Interior.
- Interior Doors
- Kitchen Cabinets
- Interior Shutters & Moldings

#### **Safety / Clean Up**

Please read the product Safety Data Sheet and product label before using product. Applications tools must be cleaned with water after use. Dispose of any leftover materials in accordance with local, state, or federal regulations.