

## Water-Based Polyurethane Catalyst/Hardener

CW-4002

### General Description

This isocyanate-based hardener provides superior moisture, scratch, mar and chemical resistance. Designed for use with Centurion™ 2K water-based polyurethane wood coatings, it can be added at a rate of 5%-15% by weight. Manufacturer recommends 15% by weight for best coating performance.

### Physical Properties

Vehicle Type	Liquid
Color	Clear
Odor	Aromatic petroleum odor
VOC	314 g/l
Flash Point	169F (closed cup)
Specific Gravity	1.08
Density	9.013 lbs./gal

### Application/Storage

Application Method	Ready to use
Mixing Instructions	To be added at a rate of 5% - 15% by weight to Centurion™ 2K products
Substrate Preparation	N/A
Application Instructions	IMPORTANT: Mix well using a power agitator prior to application. Upon application, agitate as needed to ensure product is fully blended.
Storage/Disposal	Store in a well-ventilated place. Keep container tightly closed. Dispose of contents/container at an approved waste disposal plant.

### Available Products

- 4002-Q01 1 quart
- 4002-G01 1 gallon
- 4002-G05 5 gallons

### Features/Advantages

- Superior moisture resistance
- Unmatched chemical resistance

### Recommended for:

- 2800 Series Topcoats
- 1800 Series Topcoats
- 1107 Primer
- 3020 Natural
- 2400 Series

### Safety/Cleanup

Please read the product Safety Data Sheet and product label before using product. Application tools must be cleaned with water after use. Dispose of any leftover materials in accordance with local, state or federal regulations.