

## *Water-Based Thickening Agent*

CW-9002

### General Description

When added, this water-based thickener provides increased viscosity resulting in better vertical hang. Designed for use with all Centurion™ water-based wood coatings, it can be added at a rate of 1tbs – 3tbs to all water-based products manufactured by Centurion™.

### Physical Properties

Vehicle Type	Liquid
Color	Clear to cloudy
Density	8.34 lbs/gal
VOC	None
Flash Point	110C (closed cup)
Specific Gravity	1.00
Viscosity	N/A

### Application/Storage

Application Method	Add at a ratio of 1tbs – 3tbs per gallon or as needed to achieve desired viscosity.
Mixing Instructions	Ready to use
Substrate Preparation	N/A
Application Instructions	IMPORTANT: Mix well using a power agitator prior to application. Let sit for one hour allowing thickening agent to take effect and coating to thicken up.
Handling and Storage	Avoid contact with eyes, skin and clothing. Wash hands thoroughly after handling. Keep container tightly closed. Do not breathe vapors, mist or gas.

### Available Products

- 9002-Q01 1 quart

### Features/Advantages

- Increased viscosity
- Better hang time

### Recommended for:

- 2800 Series Topcoats
- 1800 Series Topcoats
- 1107 Primer
- 1108 Primer
- 400 Series Topcoats

### Safety/Cleanup

Please read the product Safety Data Sheet and product label before using product. Application tools must be cleaned with water after use. Dispose of any leftover materials in accordance with local, state or federal regulations.