



CENTURION

CW-3026RBW O O D C O A T I N G S

Product Data Sheet

Water-Based Wood Coating

2800 Series Clear Tint Base Polyurethane Topcoat

General Description

Used as both a sealer and a topcoat, this multi-purpose coating offers excellent chemical and humidity resistance while offering outstanding color-fastness and resistance to UV degradation. The fully cured film provides superior resistance to abrasion and black heel marks, it brings a natural "warming" look to the wood. Designed for durability and performance on a variety of high-end architectural millwork, furniture, and cabinetry. Can be mixed 15% by weight with CW-4002 Hardener (based on aliphatic isocyanate) to provide a fully crosslinked film.

Physical Properties

Vehicle Type	Aqueous blend of aliphatic polyester/polycarbonate combined with crosslinked castor oil-based polyurethane.
Solids by Volume	28.05 (+/-1%)
Solids by Weight	31.65 (+/-1%)
VOC (minus exempt)	80 g/l
VOC (as supplied)	22 g/l
Specific Gravity	1.03
Viscosity	30-38 sec. Zahn #5

Application

Application Method	Can be sprayed with conventional, airless, and air assisted-airless.
Mixing Instructions	Can be mixed 15% by weight with CW-4002 Hardener (based on aliphatic isocyanate) to provide a fully crosslinked film. Centurion Thickeners and reducers can be utilized to produce desired viscosity depending on spray equipment
Substrate Preparation	The surface must be clean, dry and free of grease, oil, dirt, fingerprints and any other contamination to ensure proper adhesion. Remove any loose or peeling paint. Sand basecoat with 320-400 grit sandpaper. When used as a sealer, use 220-320 grit sandpaper in between coats. May be applied over acrylic, nitrocellulose and UV Basecoat. Test for adhesion and compatibility before full scale application.
Application Instructions	IMPORTANT: Mix well using a power agitator prior to application. Upon application, the temperature of the product, substrate, and coating should be above 65°F. Apply up to 3 coats, allowing enough drying time between coats.
Coverage	Approx. 481-545 square feet per gallon at 1 dry mil. @ 100% transfer efficiency. Actual coverage may vary depending on application technique, equipment, and weather conditions.

Curing / Drying Time Properties

Air Dying Time (77°F, 50% Humidity)	Wheel and weight	CS-17 (2) 1 kg/ea
Dust/Tack Free	Weight loss (grams)	
Sand & Recoat		13
Package		12 hours

Abrasive Resistance

Available Products

- CW-3028TB (Gloss)
- CW-3027TB (Semi-Gloss)
- CW-3026TB (Satin)
- CW-3025TB (Flat)

Features / Advantages

- Fast Drying
- Sandability
- Early Hardness Development
- Abrasion resistance
- Durability

Recommended For

- High-end Furniture
- Cabinetry
- Architectural millwork

Safety / Clean Up

Please read the product Safety Data Sheet and product label before using product. Applications tools must be cleaned with water after use. Dispose of any leftover materials in accordance with local, state, or federal regulations.

Pot Life:

When CW-4002 is added at the recommended ratio of 15% by weight, pot life will be 3 hours



CIC COATINGS | 2935 Almeta Lane | McKinney, TX 75069 | Ph: 972-384-1280 |

www.ciccoatings.com

We warrant our products to be of good quality and will replace or, at our discretion, refund the purchase price of any products proved defective. Satisfactory results depend not only upon quality products, but also upon many factors beyond our control. Therefore, except for such replacement or refund, CIC Coatings, LLC MAKES NO WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE OR MERCHANTABILITY. User shall determine the suitability of the products for the intended use and assume all risks and liability in connection therewith. The information provided herein is based on technical data that is believed to be reliable. CIC Coatings, LLC makes no representation or warranty as to the completeness or accuracy thereof and assumes no liability resulting from its use for any claims, losses, or damages of any third party and shall have no other liability with respect thereto.